

VITAWORK®



Fact sheet

TECHNICAL DATA

VITAWORK® HCL			
Colours	140 Metallic Silver/Black (similar RAL 9006 / 7021) I 02 White (similar RAL 9016)		
Dimensions	Height:	2,040 mm	
	Luminaire head (W x D x H):	542 x 370 x 32,5 mm	
	Ceiling height clearance:	> 2 m	
Weight	19 kg		
Lamp base	C-shaped		
Material	Aluminium, Steel (lamp base), Plastic (touch panel & side caps)		
Energy efficiency	A++		
Protection type	IP 20		
Protection class	I ⚡		
Illuminants			
Fitted with	LED		
Power consumption	85 W		
Light distribution	asymmetric		
Nominal luminous flux direct	2,000 lm		
Nominal luminous flux indirect	10,000 lm		
Nominal luminous flux	12,000 lm		
Luminous efficiency	> 135 lm/W		
Colour temperature (CCT)	2,700 K <-----> 6,500 K		
Colour tolerance	< 3 SDCM		
50,000 h	L85B10		
UGR	< 16		
Colour reproduction index	> 80		
Plug	Kettle plug + EU/CH/UK - plug		
Cable length	3 m		
Standby consumption	≤ 0,5 W		
VITACORE®			
Operation	via VITACORE® electronics and sensors		
Light intensity setting	Seamless or in five steps direct & indirect dimming via the touch panel		
Setting of light colour	stepless between 2,700 and 6,500 Kelvin		
Sensors	Infrared Presence Sensor & Luminosity Sensor		
Article overview			
Article number	Luminaire	Plug	Control
9281-140 I -02	VITAWORK® HCL 12 Asym. PIR KP	Kettle plug	Dimmable plus sensors
9282-140 I -02	VITAWORK® HCL 12 Asym. DIM KP	Kettle plug	Dimmable




TECHNICAL VIEW




LIGHT DISTRIBUTION CURVE

VITAWORK®



VITAWORK®



Free download at www.luctra.eu

LUCTRA

LUCTRA® is a brand of
 DURABLE · Hunke & Jochheim GmbH & Co. KG
 Westfalenstraße 77-79 · 58636 Iserlohn
 Postfach 1753 · 58634 Iserlohn
 Tel.: +49 23 71 66 24 45
 info@luctra.eu · www.luctra.eu