

## LUCTRA® FLOOR TWIN LINEAR (Art.-No.: 9237 01)



Professional LED floor lamp, double head with biologically effective light

Floor lamp with two angular heads for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Angular base, 380mm x 380mm x 8mm inclusive. Dimensions: height 2.025m and radius 100mm - 930mm. Lamp painted in black.

Both heads are equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 680 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy Efficiency A++.

Power consumption 25 W, 1,000 Lux at a height of 1.10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Switch function for separate control of the heads. Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android).

ENEC, GS, CE, Protection class II, Protection type IP20, weight 12.5kg

Manufacturer:

**LUCTRA® is a brand of**

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

[info@luctra.de](mailto:info@luctra.de) · [www.luctra.de](http://www.luctra.de)

## LUCTRA® FLOOR TWIN LINEAR (Art.-No.: 9237 02)



Professional LED floor lamp, double head with biologically effective light

Floor lamp with two angular heads for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Angular base, 380mm x 380mm x 8mm inclusive. Dimensions: height 2.025m and radius 100mm - 930mm. Lamp painted in white.

Both heads are equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 680 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy Efficiency A++.

Power consumption 25 W, 1,000 Lux at a height of 1.10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Switch function for separate control of the heads. Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android).

ENEC, GS, CE, Protection class II, Protection type IP20, weight 12.5kg

Manufacturer:

**LUCTRA® is a brand of**

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

[info@luctra.de](mailto:info@luctra.de) · [www.luctra.de](http://www.luctra.de)

## LUCTRA® FLOOR TWIN LINEAR (Art.-No.: 9237 23)



Professional LED floor lamp, double head with biologically effective light

Floor lamp with two angular heads for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Angular base, 380mm x 380mm x 8mm inclusive. Dimensions: height 2.025m and radius 100mm - 930mm. Lamp painted in silver.

Both heads are equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 680 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy Efficiency A++.

Power consumption 25 W, 1,000 Lux at a height of 1.10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Switch function for separate control of the heads. Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android).

ENEC, GS, CE, Protection class II, Protection type IP20, weight 12.5kg

Manufacturer:

**LUCTRA® is a brand of**

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

[info@luctra.de](mailto:info@luctra.de) · [www.luctra.de](http://www.luctra.de)

## LUCTRA® FLOOR TWIN RADIAL (Art.-No.: 9238 01)



Professional LED floor lamp, double head with biologically effective light

Floor lamp with two round heads for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with auto-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Round base, 380mm x 380mm x 8mm inclusive. Dimensions: height 2.025m and radius 100mm - 730mm. Lamp painted in black.

Both heads are equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50.000h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 680 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 25 W, 1,000 Lux at a height of 1.10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Switch function for separate control of the heads. Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android).

ENEC, GS, CE, Protection class II, Protection type IP20, weight 12.5kg

Manufacturer:

**LUCTRA® is a brand of**

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

[info@luctra.de](mailto:info@luctra.de) · [www.luctra.de](http://www.luctra.de)

## LUCTRA® FLOOR TWIN RADIAL (Art.-No.: 9238 02)



Professional LED floor lamp, double head with biologically effective light

Floor lamp with two round heads for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with auto-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Round base, 380mm x 380mm x 8mm inclusive. Dimensions: height 2,025mm and radius 100mm - 730mm. Lamp painted in white.

Both heads are equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50.000h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 680 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 25 W, 1,000 Lux at a height of 1.10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Switch function for separate control of the heads. Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android).

ENEC, GS, CE, Protection class II, Protection type IP20, weight 12.5kg

Manufacturer:

**LUCTRA® is a brand of**

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

[info@luctra.de](mailto:info@luctra.de) · [www.luctra.de](http://www.luctra.de)

## LUCTRA® FLOOR TWIN RADIAL (Art.-No.: 9238 23)



Professional LED floor lamp, double head with biologically effective light

Floor lamp with two round heads for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with auto-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Round base, 380mm x 380mm x 8mm inclusive. Dimensions: height 2,025mm and radius 100mm - 730mm. Lamp painted in silver.

Both heads are equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50.000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 680 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 25 W, 1,000 Lux at a height of 1.10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Switch function for separate control of the heads. Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android).

ENEC, GS, CE, Protection class II, Protection type IP20, weight 12.5kg

Manufacturer:

**LUCTRA® is a brand of**

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77-79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

[info@luctra.de](mailto:info@luctra.de) · [www.luctra.de](http://www.luctra.de)