

LUCTRA® FLOOR LINEAR (Art.-No.: 9235 01)



Professional LED floor lamp with biologically effective light

Floor lamp with angular head for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Angular base, 380mm x 380mm x 8mm inclusive. Dimensions: height 1.200mm – 1.900mm and radius 100mm - 800mm. Lamp painted in black.

Equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 900 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 10.5 W, 1,000 Lux at a height 1,10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1,8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Boost- Function ON/OFF (max. light strength of cold white LEDs for 30 Min.) Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android). 2 integrated USB charging ports 5V charging function.

ENEC, GS, CE, Protection class II, Protection type IP20, weight 11.5kg

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

info@luctra.de · www.luctra.de

LUCTRA® FLOOR LINEAR (Art.-No.: 9235 02)



Professional LED floor lamp with biologically effective light

Floor lamp with angular head for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Angular base, 380mm x 380mm x 8mm inclusive. Dimensions: height 1.200mm – 1.900mm and radius 100mm - 800mm. Lamp painted in white.

Equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 900 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 10.5 W, 1,000 Lux at a height 1,10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1,8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Boost- Function ON/OFF (max. light strength of cold white LEDs for 30 Min.) Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android). 2 integrated USB charging ports 5V charging function.

ENEC, GS, CE, Protection class II, Protection type IP20, weight 11.5kg

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

info@luctra.de · www.luctra.de

LUCTRA® FLOOR LINEAR (Art.-No.: 9235 23)



Professional LED floor lamp with biologically effective light

Floor lamp with angular head for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Closed body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Angular base, 380mm x 380mm x 8mm inclusive. Dimensions: height 1.200mm – 1.900mm and radius 100mm - 800mm. Lamp painted in silver.

Equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 900 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 10.5 W, 1,000 Lux at a height 1,10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1,8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Boost- Function ON/OFF (max. light strength of cold white LEDs for 30 Min.) Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android). 2 integrated USB charging ports 5V charging function.

ENEC, GS, CE, Protection class II, Protection type IP20, weight 11.5kg

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

info@luctra.de · www.luctra.de

LUCTRA® FLOOR RADIAL (Art.-No.: 9236 01)



Professional LED floor lamp with biologically effective light

Floor lamp with round head for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Open body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Round base, 380mm x 380mm x 8mm inclusive. Dimensions: height 1,200mm – 1,900mm and radius 100mm - 700mm. Lamp painted in black.

Equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 900 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 10.5 W, 1,000 Lux at a height 1,10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Boost- Function ON/OFF (max. light strength of cold white LEDs for 30 Min.) Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android). 2 integrated USB charging ports 5V charging function.

ENEC, GS, CE, Protection class II, Protection type IP20, weight 11.5kg

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

info@luctra.de · www.luctra.de

LUCTRA® FLOOR RADIAL (Art.-No.: 9236 02)



Professional LED floor lamp with biologically effective light

Floor lamp with round head for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Open body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Round base, 380mm x 380mm x 8mm inclusive. Dimensions: height 1,200mm – 1,900mm and radius 100mm - 700mm. Lamp painted in white.

Equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 900 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 10.5 W, 1,000 Lux at a height 1,10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5 W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Boost- Function ON/OFF (max. light strength of cold white LEDs for 30 Min.) Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android). 2 integrated USB charging ports 5V charging function.

ENEC, GS, CE, Protection class II, Protection type IP20, weight 11.5kg

Manufacturer:

LUCTRA® is a brand of

DURABLE • Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 • 58636 Iserlohn

Postbox 1753 • 58634 Iserlohn

Telephone +49 2371 662-445

info@luctra.de • www.luctra.de

LUCTRA® FLOOR RADIAL (Art.-No.: 9236 23)



Professional LED floor lamp with biologically effective light

Floor lamp with round head for direct lighting, by turning 90° | 185° indirect lighting possible. Adjustment of light with self-locking hinges minimum 50,000 cycles. Open body made from aluminum and lamp base made of steel. Head with open cooling fins for an optimal temperature management. Operating temperature <40°C at (ta) 25°C ambient temperature. Round base, 380mm x 380mm x 8mm inclusive. Dimensions: height 1,200mm – 1,900mm and radius 100mm - 700mm. Lamp painted in silver.

Equipped with 2 cold white and 2 warm white high-power LEDs with a burning life of L80/B10 (50,000 h), for individual adaption of the colour temperature 2,700-6,500 Kelvin. Luminous flux of luminaire: 900 Lumen. Colour rendering Ra/CRI>80. Colour tolerance SDCM<2. Energy efficiency A++.

Power consumption 10.5 W, 1,000 Lux at a height 1,10m. Flexible supply line from lamp to converter (Power supply unit) black with Europlug & BS 1363 (british 3-pin)-plug, length 1.8m. Rated voltage: 100-240V, 50/60Hz. Stand-by consumption < 0.5W.

Control of the functions by capacitive touch panel made of glass with patented VITACORE® electronics: Standby ON / OFF, stepless light strength setting and light colour from 2,700K to 6,500K. Boost- Function ON/OFF (max. light strength of cold white LEDs for 30 Min.) Possibility of adaption to the personal daily rhythm with free VITACORE®-App. With Bluetooth connection for LE-enabled Smartphones and Tablets (IOS/Android). 2 integrated USB charging ports 5V charging function.

ENEC, GS, CE, Protection class II, Protection type IP20, weight 11.5kg

Manufacturer:

LUCTRA® is a brand of

DURABLE · Hunke & Jochheim GmbH & Co. KG

Westfalenstraße 77–79 · 58636 Iserlohn

Postbox 1753 · 58634 Iserlohn

Telephone +49 2371 662-445

info@luctra.de · www.luctra.de